

Decolastic Top Coat Finish

Description

- It is a 100% acrylic based coating designed smooth, without aggregate, to provide a highly elastomeric, durable, and weather-resistant, decorative finish.
- Decolastic Top Coat Finish is a rollable, sprayable or brushable coating that will withstand thermal expansion and contraction without delamination.
- Because it is an acrylic elastomeric coating, it will bridge cracks up to 1/16".
- It is available in 64 standard colors and an infinite number of custom colors.
- This fade resistant ready-mix coating is very application friendly.

Preparation

- Decolastic Top Coat Finish has been formulated to be applied over all Decolastic finish textures as well as conventional stucco brown coat, masonry block, poured on precast concrete, and plaster.
- The entire surface should be clean and free of any contaminates.
- Surface and air temperature should be at a minimum of 45°F during and for at least 24 hours after the application.

Mixing

- Using a Goldblatt Jiffy Mixer, or equivalent, mix the finish until a uniform consistency is attained.

Application

- Decoplast Top Coat Finish may be applied by roller, spray or brush.
- When spraying, use airless equipment with a .035 minimum orifice and a filter only at the inlet side.
- When wet, apply a maximum of 24 mils per coat, preferably 16 mils per application minimum.
- Apply Decolastic Top Coat Finish at a rate of 100 square feet per gallon.

Cleaning

- Clean equipment and containers with water as quickly as possible.

Cautions

- Protect the material from freezing.
- Finishes must be applied at or above 45°F.
- Do not apply on damp surfaces or when rain is forecasted.
- Consult the manufacturer's Material Safety Data Sheets.

Product Data

Coverage

- 325 - 600 square feet per 5 gallon pail, with a rate of coverage varying due to the substrate's composition.

Drying Time

- Recommended drying time for Top Coat Finish is approximately 2 hours. This estimate is based on optimum weather conditions of 70°F, with 55% relative humidity.
- Drying times will vary based on temperature and humidity.

Availability

- Decoplastic Top Coat Finish is available only at authorized Decoplast distributors.

Warranty

- Consult your nearest Decoplast professional for details.

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Decoplast, Inc.®

(516) 354-4397 • www.decoplast.com

352 Franklin Ave, Franklin Square, New York, 11010