

## SUBMITTAL SHEET 07240

### Decoplast *Faux Brick* Finishes

#### Description

- The Decoplast *Faux Brick* is a 100% acrylic polymer material engineered to provide a durable, weather-resistant and decorative finish.
- Decoplast *Faux Brick* finishes are architecturally decorative and will withstand thermal expansion and contraction without delamination.
- This custom -colored finish is available in an infinite number of custom matched colors.

#### Preparation

- Decoplast *Faux Brick* finishes have been formulated to be applied over all Decoplast base coats as well as conventional stucco brown coat, masonry block, poured precast concrete and plaster.
- The entire surface should be clean and free of any contaminates.
- Surface and air temperature should be at a minimum of 45°F during and at least 24 hours after application. The adhesive stencil will bond more securely to a warmer surface.

#### Mixing

- Using a Goldblatt Jiffy Mixer, or equivalent, mix the finish until uniform consistency is attained.
- Based on job site conditions, it may be necessary to add up to 8 ounces of clean potable water to the mixture.
- Add the same volume of water to each pail to ensure color and texture consistency.

#### Application

- Decoplast *Faux Brick* finishes are applied in a two application process using a clean stainless steel trowel and short nap roller.

- With a short knap roller apply Decoplast Top Coat to the entire field to match desired grout color.
- After the Top Coat is dry, peel adhesive backed brick stencil pattern and stick to Top Coat revealing running bond grid.
- By steel trowel apply Faux Brick finish then remove brick stencil. Use care when removing pattern not to damage newly applied finish. A small paint brush may be used to restore grout color areas that may possibly be damaged during the grid removal.

### **Cleaning**

- Clean equipment and containers with water immediately after use.

### **Cautions**

- Protect work from freezing.
- Finishes must be applied at or above 45°F.
- Handle with care.
- Consult the manufacturer's Material Safety Data Sheets.

### **Availability**

- Decoplast *Faux Brick* finishes are available only at authorized Decoplast distributors.

### **Warranty**

- Consult your nearest Decoplast professional for details.

#### **Disclaimer**

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.