

ADEX Non-Cementitious Adhesive

Description

- The Decoplast ADEX is an integral part of the Decoplast coatings line.
- ADEX is an adhesive designed to bond Decoplast foam insulation board to exterior gypsum board as well as approved unpainted exterior plywood. ADEX maybe used on alternate substrates, see your Decoplast representative for further information.

Preparation

- The entire approved substrate must be clean and free of any contaminates.
- The surface and air temperature should be at a minimum of 45°F during and for at least 24 hours after the application.

Mixing

- Using a Goldblatt Jiffy mixer, or equivalent, mix the coating until a uniform consistency is attained.

Application

- **Decoplast Approved Substrate:**
Decoplast ADEX is applied directly to the back of Decoplast insulation foam board. With a stainless steel 3/8" "U" notched trowel ADEX should be applied in even lines. The coated foam insulation should be placed on the wall surface slightly away from its final position. The foam board should be slid into position spreading the ADEX coating between the foam board and substrate. (Fasteners may be used to hold boards in place on contoured substrates until ADEX is cured)

Physical Properties

Bond Strength – ASTM C297..... 56 psi

Flexibility: Will accommodate reasonable movement of wood sheathing due to expansion and contraction without reduction of bond.

Vapor Transmission: Does not create a vapor barrier when installed properly.

Cleaning

- Clean equipment and containers with water immediately after use.

Cautions

- Protect the material from freezing.
- Handle with care.
- Consult the manufacturer's Material Safety Data Sheets.

Availability

- ADEX Non-Cementitious Adhesive is available only at authorized Decoplast distributors.

Coverage

- 300 square feet per 5 gallon pail
- Pail weight: 69LBS

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Decoplast, Inc.®

(516) 354-4397 • www.decoplast.com

352 Franklin Ave, Franklin Square, New York, 11010