

Speed Coat - Moisture Barrier & Adhesive

Description-

- The Decoplast Speed Coat is an integral part of the Decoplast coatings line.
- This unique, breathable coating has been engineered to span seams and cracks in approved substrates up to 1/16" of an inch. Speed Coat has been designed as a weather resistive barrier as well as a high performance adhesive. As a one step process, Speed Coat will significantly increase job progress.

Preparation

- The entire approved substrate must be clean and free of any contaminates.
- The surface and air temperature should be at a minimum of 45°F during and for at least 24 hours after the application.

Mixing

- Using a Goldblatt Jiffy mixer, or equivalent, mix the coating until a uniform consistency is attained.

Application

- Decoplast Approved Substrate:
Decoplast Speed Coat is to be applied to all board joints at a rate of 24 mils. This may be applied by trowel, roller, spray or brush. While the Speed Coat is wet embed Decoplast joint cloth. The joint cloth shall not be visible upon completion of this process.
- By trowel, (working in small sections) Speed Coat is to be applied to the substrate at a rate thick enough so not to see the substrate beneath (1/8" minimum). Note: It is important that the entire substrate is coated evenly, creating a monolithic barrier, encapsulating the entire substrate.
- While the Speed Coat is wet apply Decoplast EPS foam in a running bond pattern as per the system details.
- Decoplast Speed Coat can also be used with ant Decoplast system as a moisture barrier or as an integral part of the Decoplast "Notched" and "Deco-Drain" moisture drainage systems.

Physical Properties

- Water Vapor Permeability – ASTM E96.....5.6 perms
- Elongation – ASTM D412.....127%
- Early Grab – RH #902.....20 minutes
- Freeze / Thawpasses 7 cycles

Cleaning

- Clean equipment and containers with water immediately after use.

Cautions

- Protect work from freezing.
- Handle with care.
- Consult the manufacturer's Material Data Safety Sheets.

Availability

- Decoplast Speed Coat is available only at authorized Decoplast distributors.

Coverage

- Moisture Barrier / adhesive: 200 sq. ft.
- Moisture Barrier: 275 sq. ft.
- Pail weight:

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Decoplast, Inc.®

(516) 354-4397 • www.decoplast.com

352 Franklin Ave, Franklin Square, New York, 11010