

SUBMITTAL SHEET 07240

Deco-Shield "Air/Vapor Barrier Tape System"

Description

- Deco-Shield is a superior self-adhering, air moisture barrier for vertical and horizontal EIFS/Stucco systems. This tape is a 30 mil SBS modified rubberized asphalt membrane with a polyester top surface. This polyester surface enhances the adhesion of Decoplast foam when applied over it. This tape is self sealing when penetrated with mechanical fasteners.

Preparation

- Surface should be clean, dry and free of dirt and foreign matter. Deco-Shield should be applied at a temperatures above 45°F. For difficult adhesive surface conditions it is recommended that the use of Deco-Shield Primer 6000 be applied just prior to adhering the Deco-shield tape.

Application

- Cut a piece of Deco-Shield tape in a length that can be easily handled. Begin the application by removing approximately 12 inches of the release paper and center the tape against the surface and continue pulling off the release paper while smoothing the tape in place. Rolling the tape will help to ensure a water tight seal and minimize trapping air beneath the tape.

Note: When applying the tape to masonry or concrete, see your Decoplast representative for the proper primer needed.

Substrates

- Exterior Gypsum
- Exterior Grade Plywood
- Metal

- Styrene
- Polyethylene

Properties

Color	White- Top Surface Black- Bottom Surface	
Thickness	30 mil	
Tensile Strength (Polyester Fabric)	1400 psi	ASTM D412
Elongation (Rubberized Asphalt)	Over 500%	ASTM D412
Moisture Barrier Transmission Rate	0.1 perm max	ASTM E96

Cleaning

- Clean equipment and containers with water immediately after use.

Cautions

- Do not leave exposed to sunlight for more than 6 weeks.
- Avoid inhaling dust.
- Handle with care.
- Consult the manufacturer's Material Safety Data Sheets.

Availability

- Deco-Shield is available only at authorized Decoplast distributors.

Warranty

- Consult your nearest Decoplast professional for details.

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.