

Decolastic Textured Finishes

Description

- This 100% acrylic polymer material is engineered to provide a highly elastic, durable, weather-resistant, and decorative finish.
- Decolastic textured finishes are very architecturally friendly in their design and will withstand thermal expansion and contraction without delamination.
- It is available in 64 standard colors and an infinite number of custom colors.
- These fade resistant ready-mix textures are very application friendly.

Preparation

- Decolastic textured finishes have been formulated to be applied over all Decoplast base coats as well as conventional stucco brown coat, masonry block, poured on precast concrete and plaster.
- The entire surface should be clean and free of any contaminants.
- Surface and air temperature should be at a minimum of 45°F during and at least 24 hours after the application.

Mixing

- Using a Goldblatt Jiffy Mixer, or equivalent, mix the finish until uniform consistency is attained.
- Based on job site conditions, it may be necessary to add 8 ounces of clean potable water to the mixture.
- Add the same volume of water to each pail to ensure color and texture consistency.

Application

- Decolastic textured finishes are applied in a single coat using a clean stainless steel trowel.
- Apply the finish in a uniform thickness slightly thicker than the size of the largest aggregate.
- Horizontally level the rough applied finish to a thickness no greater than the size of the largest aggregate.
- The final finish will be achieved with a plastic trowel, applying light pressure in a circular method.
- This application can be over conventional stucco brown coat.
- Note: It is recommended to apply a coat of Decolastic primer prior to the finish application.

Cleaning

- Clean equipment and containers with water immediately after use.
- Completely flush spray equipment with water.
- Allow water to remain in the lines until the equipment is ready for its next use.

Cautions

- Protect the material from freezing.
- Finishes must be applied at or above 45°F.
- Do not apply on damp surfaces or when rain is forecasted.
- Consult the manufacturer's Material Safety Data Sheets.

Product Data

Coverages below are only approximate and may vary with texture and applicator's technique.

- | | |
|--------------|--------------------------|
| - Ispica: | varies with texture |
| - Genova: | 150-170 sq. ft. per pail |
| - Trieste: | 100-125 sq. ft. per pail |
| - San Remo: | 80-100 sq. ft. per pail |
| - Taormina: | 160-180 sq. ft. per pail |
| - Graffiato: | 150-170 sq. ft. per pail |

Drying Time

- It is recommended to allow finish application approximately 24 hours to dry. This estimate is based on optimum weather conditions of 70°F, with 55% relative humidity.
- Drying times will vary based on temperature and humidity.

Availability

- Decolastic textured finishes are available only at authorized Decoplast distributors.

Warranty

- Consult your nearest Decoplast professional for details.

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Decoplast, Inc.®

(516) 354-4397 • www.decoplast.com

352 Franklin Ave, Franklin Square, New York, 11010