

Fiber Reinforcing Meshes

Description

- Fiberglass fabric reinforcement woven mesh is specifically treated to resist alkaline and impact as well as being flame retardant.
- Available in seven specific weights, it is designed to achieve specified impact resistance.

Product Style Description	U.S. OZ / Sq. Yd.	International Grm. / Sq. M	Manufactured Size	Packaging
- Detail:	4.5 oz	155 g/m ²	9.5" x 150'	16 rolls/box
- Standard:	4.5 oz	155 g/m ²	38" x 150'	4 rolls/box
- High Standard:	6.0 oz	207 g/m ²	38" x 150'	4 rolls/box
- Intermediate:	10.0 oz	346 g/m ²	38" x 75'	4 rolls/box
- Armor 15:	14.0 oz	484 g/m ²	38" x 75'	2 rolls/box
- Armor 20:	20.0 oz	692 g/m ²	38" x 75'	2 rolls/box
- Corner:	7.2 oz	249 g/m ²	9.5" x 150'	4 rolls/box

Storage

- Store in a cool dry place (above 45°F).
- Keep away from sunlight.

Availability

- Decoplast Fiber Reinforcing Mesh styles are available only at authorized Decoplast distributors.

Warranty

- Consult your nearest Decoplast professional for details.

Disclaimer

Decoplast, Inc. will not be held liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current manufacturers instructions or other than the intended use. Our liability is expressly limited to replacement of defective goods only. Any claim will be considered waived unless made in writing to us within thirty days from the date it was discovered.

Decoplast, Inc.®

(516) 354-4397 • www.decoplast.com

352 Franklin Ave, Franklin Square, New York, 11010