



The Stucco Veneziano Collection

TECHNICAL DATA SHEET DECO-SEAL (Exterior Sealant)

FEATURES AND RANGE OF USE

DECO-SEAL is a silicone filler with a base of selected siloxane and high penetration surfactants. It is in a solution which makes the wall substrate highly water-repellent and so, very resistant to nature's elements. DECO-SEAL is suitable to protect exterior surfaces without modifying the natural aesthetic aspect.

RULES FOR USE - PREPARATION OF BASE

Newly plastered wall surfaces: Clean thoroughly, removing any trace of dust, dirt, or any loose particles. Make sure that the wall surface is perfectly dry and free of saline efflorescence, mold and other pathogen micro-organisms.

APPLICATION

DECO-SEAL is a ready-to-use and can be applied with a paintbrush, roller or spray. Treat the surfaces uniformly, applying DECO-SEAL in two coats so as to saturate the substrate.

Do not apply DECO-SEAL in below freezing temperatures.
Clean all tools thoroughly after use.

TECHNICAL DATA

Specific weight:	- 0.9kg/l
Viscosity:	- 30-40 cPs at 20°C
Minimum temperature to film:	- 10 C at 60% R.H.
Resistance to alkalis:	- non-saponifiable to the lime and the aqueous solution of NaOH at 10%
Resistance to inclemency of weather:	- excellent

CONSUMPTION

It is not possible to predetermine the consumption of DECO-SEAL since it depends on the use and application of product according to absorption properties of the substrate.

STORAGE

DECO-SEAL is available in 10kg containers. Preserve the product from excessive heat and cold. Keep product in its original container and within a temperature range of 5°C to 30°C. Remember to close the container well after each use.